

GO-GO[®] *es* 2

3-WHEEL SCOOTER

OUTSTANDING
VALUE.
EXCEPTIONAL
DURABILITY.

The Go-Go[®] ES 2 from Pride[®] combines exceptional value and easy transportation together in a compact, lightweight package. The stylish Go-Go ES 2 has a weight capacity of 250 lbs., variable motor speeds and a convenient canvas basket located on the tiller.



Go-Go[®] ES 2 3-wheel




PRIDE[®] MOBILITY SCOOTERS
LIVE YOUR BEST[®]

pridemobility.com



SPECIFICATIONS

GO-GO® ES 2

Weight capacity:	250 lbs.
Maximum speed ¹ :	Up to 4 mph
Ground clearance ² :	1.5" at motor
Turning radius ² :	31"
Overall length ² :	36.75"
Overall width ² :	19.5"
Front tires:	2" x 7.5" solid
Rear tires:	3" x 7.5" solid
Range per charge ^{2,4} :	Up to 6.8 miles
Total weight without batteries:	58.4 lbs.
Heaviest piece when disassembled:	41.4 lbs. (scooter base)
Standard seating:	Type: Foldable, compact, vinyl-covered molded plastic Weight: 17 lbs. Material: Black Vinyl Dimensions: Width: 17" Depth: 15"
Motor output:	24-volt DC motor, sealed mini-transaxle
Brakes:	Electronic, regenerative and electromechanical
Battery requirements ^{3,5} :	(2) 12V deep-cycle Size: (2) 12 AH Weight: 9 lbs. each
Battery charger:	Off-board, 2 amp
Color:	 Black

FEATURES

- Two speed settings - high and low (indoor/outdoor)
- Modular design for easy serviceability
- Removable front canvas basket
- Lightweight, one-piece frame for added stability and easy portability



Mobility Made Easy. Pride offers a variety of lifts to transport your mobility product with ease. To find a compatible lift for your vehicle and mobility product, use our new Lift Finder application at pridemobility.com/lift-finder/

- ¹ Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition. These specifications can be subject to a variance of (+/- 10%).
- ² Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).
- ³ AGM or gel cell type required.
- ⁴ Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
- ⁵ Battery weight may vary based on manufacturer.

NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.



PRIDE® MOBILITY SCOOTERS
LIVE YOUR BEST®

(US) 800-800-8586 • (Canada) 888-570-1113
pridemobility.com