

GO-GO[®]

LX WITH CTS SUSPENSION

3 & 4-WHEEL SCOOTER

THE SMOOTHEST RIDE IN TRAVEL MOBILITY



Comfort-Trac Suspension

The Go-Go[®] LX with Comfort-Trac Suspension (CTS) brings a whole new level of comfort and performance to travel mobility scooters. Pride's industry first CTS technology incorporates advanced suspension components for improved absorption over various terrains. The Go-Go LX with CTS offers a 300 lb. weight capacity, a per charge range up to 10.5 miles and a maximum speed of 4.4 mph. Standard features include feather-touch disassembly—which easily disassembles into 5 lightweight pieces for convenient transport and storage, wraparound delta tiller with charger port, non-scuffing black tires, LED headlight and front basket. Optional color shrouds available.



Go-Go[®] LX with CTS Suspension
4-wheel shown with
optional under seat storage



Go-Go[®] LX with CTS Suspension
3-wheel
(Shown with optional Pearl Pink shrouds)

PRIDE[®] MOBILITY SCOOTERS
LIVE YOUR BEST[®]

pridemobility.com



SPECIFICATIONS

GO-GO® LX WITH CTS SUSPENSION

3W: S50LX 4W: S54LX

Weight capacity:	300 lbs.
Maximum speed ¹ :	Up to 4.4 mph
Ground clearance ² :	1.5" at motor
Turning radius:	3W: 33" 4W: 44.75"
Overall length ² :	3W: 39.75" 4W: 41"
Overall width ² :	20.5"
Front tires:	3W: 2" x 8" solid 4W: 2" x 7" solid
Rear tires:	2.5" x 8" solid
Range per charge ^{1,4} :	3W: Up to 5.9 miles (12 AH) 4W: Up to 5.5 miles (12 AH) 3W: Up to 9.44 miles (18 AH) 4W: Up to 10.5 miles (18 AH)
Total weight w/out batteries ⁵ :	3W: 85.4 lbs. 4W: 87.4 lbs.
Heaviest piece when disassembled:	3W: 34 lbs. (front section) 4W: 36.6 lbs. (front section)
Standard seating:	Type: Foldable, compact, vinyl-covered molded plastic Weight: 23 lbs. Material: Black Vinyl Dimensions: Width: 17", Depth: 17"
Motor output:	24-volt DC motor, sealed mini-transaxle
Brakes:	Regenerative and electromechanical
Battery requirements ^{3,5} :	(2) 12V Deep-cycle Size: (2) 12 AH-9 lbs. each or (2) 18 AH (optional)-14lbs. each Weight: 12AH: 20 lbs. per battery pack, 18 AH: 29.5 lbs. per battery pack
Battery charger:	Off-board, 2 amp

Color: Interchangeable Shrouds



Red



Blue

Optional



Orion Yellow



Onyx Black



Pearl Pink Sunburst Orange



FEATURES

- Comfort-Trac front and rear suspension for added comfort
- Feather-touch disassembly permits simple frame separation with only one hand
- Frame easily disassembles into 5 lightweight pieces for convenient transport and storage
- Stylish, lightweight, non-scuffing black low-profile tires
- Front frame-mounted seat post offers maximum stability
- Microprocessor-based controller offers optimal power management and added safety features
- Standard front tiller-mounted basket
- Convenient off-board dual voltage charger can charge battery pack on-board or off-board
- Charger port in tiller
- Includes 2 sets, 1 each of Red and Blue interchangeable color shroud panels
- Optional color shroud panels also available: Onyx Black, Orion Yellow, Pearl Pink, Sunburst Orange
- Optional under seat storage (assembly required)

Pride® Lifts & Ramps

Compatible Lifts:

- Backpacker® Plus
- Backpacker® AVP
- Olympian
- Outlander Full Platform
- Outlander TM

¹ Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition. These specifications can be subject to a variance of (+/- 10%).

² Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).

³ AGM or gel cell type required.

⁴ Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.

⁵ Battery weight may vary based on manufacturer.

NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.



PRIDE® MOBILITY SCOOTERS
LIVE YOUR BEST®