

| Part                | Description                                    | Usage |
|---------------------|--|-------|
| <b>0033-B164-08</b> | Bracket, Mounting, 758C Indicator              | 1.0   |
| <b>0065-B352-0A</b> | Latch Weldment                                 | 1.0   |
| <b>0065-B359-08</b> | Latch Plate                                    | 1.0   |
| <b>0065-B373-0A</b> | Latch Block, Lower                             | 1.0   |
| <b>0065-B374-08</b> | Latch Spacer                                   | 2.0   |
| <b>0065-B403-0A</b> | Cable, 758C Indicator, 6875/6550 Scales        | 1.0   |
| <b>0065-B442-08</b> | Latch Shaft                                    | 1.0   |
| <b>574R918</b>      | WHEEL 4" X 1" X 5/16" BORE                     | 2.0   |
| <b>6028-0093</b>    | Pin, Hitch, 1/4" x1" , with Split Ring         | 1.0   |
| <b>6028-0094</b>    | Split Ring .825 OD X .707 ID X .110            | 1.0   |
| <b>6540-1070</b>    | Foam, Grip, 0.89" ID, BLACK                    | 2.0   |
| <b>6540-1105</b>    | Wheel, Rubber, 2"x 13/16", 1/4" Shaft          | 2.0   |
| <b>6540-1122</b>    | Foot, Rubber, .81 Diameter, Adhesive           | 4.0   |
| <b>6540-1149</b>    | Plug, 1" D Tubing /14-20 Ga.                   | 8.0   |
| <b>6680-0031</b>    | Washer, Flat, #4, Nylon                        | 1.0   |
| <b>6680-1014</b>    | Chain, Twist Link, #4, Zinc Plated             | 1.0   |
| <b>LFB-250M</b>     | Load Cell, Shear Beam, 125 Kg, Stainless Steel | 4.0   |