# **Material Safety Data Sheet**

# **Section 1 Product and Company Indentification**

Data Sheet Number: PM2015043

**Product Number:** C-12VD **Issue date:** October 05, 2015

**Total pages:** 5

Product: DC-DC Converter/Adaptor

**Description:** 12V Converter for Respironics Dream Station

Designated for rechargeable: Yes

Manufactured by: Ningbo Hi-Tech Zone Polarmate

390 Guanghua Road Ningbo, China 315040

Phone Number (Technical Contact): +86-574-87900836 Emergency Phone Number: +86-13805861669

Section 2 Composition/Information on Ingredients Composition/Information on Ingredients

Substance Approximate Percent of Total Weight

Item	Component	Weight %	CAS#
1	ABS Resin	30.2	N/A
2	Aluminum	4.9	7429-90-5
3	Polyvinyl Chloride	9	N/A
4	Copper	4.5	7440-50-8
5	Remaining inert materials	51.4	N/A

#### **Section 3 Hazards Indentification**

#### **Primary Routes of Entry:**

- ► Skin contact, Skin absorption, Eye contact, Inhalation, and Ingestion : NO Symptoms of Exposure:
- ▶ Skin contact: No effect under routine handling and use.
- ▶ Skin absorption: No effect under routine handling and use.
- ▶ Eye contact: No effect under routine handling and use.
- ▶Inhalation: No effect under routine handling and use.
- ▶ Reported as Carcinogen: Not applicable

This product described in this Product Safety Data Sheet are sealed units which are not hazardous when used according to the recommendations of the manufacturer and as long as their integrity is maintained.

Do not open, disassemble, expose to water, or expose to temperatures above the declared operating temperature range of the product. Fire, burn hazards may occur in such abuse conditions.

Keep this product away from small children. International Standard IEC 60086-4 contains more detailed information on safety of lithium batteries.

#### **Section 4 First-aid Measures**

#### Inhalation, Eye contact and Skin contact: No health hazard.

## In case of leaking or accidentally opened Lithium ion cells contained in this product

▶ Skin Contact: Immediately wash off skin with plenty of water for at least 15 minutes.

Remove contaminated clothing and wash before reuse.

In severe cases obtain medical attention.

▶ Eye Contact: Immediately flush with plenty of water for at least 15 minutes.

In severe cases obtain medical attention.

▶ Inhalation: Leave area immediately and move to fresh air. Rest and keep warm.

In severe cases obtain medical attention.

▶ **Ingestion:** Rinse mouth and surrounding area thoroughly with water.

Drink milk/water and induce vomiting. Seek immediate medical attention.

In severe cases obtain medical attention.

## **Section 5 Fire-fighting Measures**

#### **General Hazard:**

Cells contained in this product are not flammable but organic material will burn if the cell is incinerated.

Combustion products include, but are not limited to hydrogen fluoride, carbon monoxide and carbon dioxide.

#### **Extinguishing Media:**

- ▶In case of fire, use CO<sub>2</sub> or dry chemical extinguisher suitable for the materials that are burning.
- ▶ For fire in an adjacent area, water can be used.

#### **Special fire fighting instructions:**

- ▶ If possible, remove this product from fire fighting area. If heated above 120 °C, cell(s) contained in this product can explode/vent.
- ▶ Dry chemical type extinguishers have only limited extinguishing potential.

#### **B. Fire Fighting Equipment:**

▶ Use NIOSH/MSHA approved full-face self-contained breathing apparatus (SCBA) with full Protective gear.

# **Section 6 Accidental Release Measures**

When housing of cells contained in this product is damaged, small amounts of electrolyte may leak. Seal this product air tight in a plastic bag or suitable containers, adding some dry sand, chalk (CaCO<sub>3</sub>) or lime (CaO) powder or Vermiculite. Electrolyte traces may be wiped off dryly using household paper. Rinse with water afterwards.

#### **Section 7 Handling and Storage**

- ▶ No special protective requirement for handling this product.
- ► Storage within temperature range from -20 °C to 60°C.
- ▶ Do not place near heating equipment, nor expose to direct sunlight for long periods.
- ► Store this product in clean environment without chemical vapour or excessive humidity. Elevated temperatures can result in reduced this product service life.

#### **Section 8 Exposure Controls/Personal Protection**

## **Engineering controls:**

Keep away from heat and naked flame. Store in a cool and dry place.

## Personal protection:

- ▶ Respirator: None required under normal use conditions. SCBA is required in the event of a fire.
- ► Hand protection: None required under normal use conditions.
- ▶ Eye/face protection: None required under normal use conditions.

#### **Section 9 Physical and Chemical Properties**

State	Solid
Odor	N/A
pH	N/A
Vapor pressure	N/A
Vapor density	N/A
Boiling point	N/A
Solubility in water	Insoluble
Specific gravity	N/A
Density	N/A

## Section 10 Stability and Reactivity

This product is stable under the conditions described in Section 7.

Reactivity: None

**Incompatibilities:** None during normal operation. Avoid exposure to heat, open flame and corrosives. Hazardous decomposition products: None during normal operating conditions.

#### Conditions to avoid:

- ▶ Do not heat and expose uder the open flame or incinerate this product.
- ▶ Do not disassemble or modify this product.
- ▶ Do not place this product under high temperature conditions such as near a fire.
- ▶ Do not allow this product to get wet or be immersed in water.

## **Section 11 Toxicological Information**

This product does not elicit toxicological properties during routine handling and use.

Sensitization: Teratogenicity: Reproductive toxicity: Acute toxicity:

N/A N/A N/A

This product does not contain any kinds of the following substances and halogen-type flame retardants including Chlorine and Bromide type harmful flame retardants which are listed in Appendix of TCO documents and relevant international ECO requirements:

Polybrominated Biphenyls (PBB)

Polybrominated Biphenyl Ethers (PBBE)

Polybrominated Biphenyl Oxides (PBBO)

Polybrominated Diphenylethers (PBDE)

Polychlorinated Biphenyl (PCB)

Polychloronated Diphenylethers (PCDE)

Tetrabromophisphenol (TBBPA)

Asbestos, Antimonytrioxide, Dioxine

None of the following substances will be exposed, leaked, or emitted during transportation, storage or any operation and any temperature condition:

Chlorinated Fluorohydrocarbon (FCKW)

Acrylonitride

Styrol

Phenol

Benzol

Mercury of greater than 0.0001 wt% for alkaline battery

Mercury of greater than 0.0005 wt% for other battery

Lithium content of greater than 0.5g/battery cell

Cadmium, lead, and other harmful heavy metal

And will comply with the regulation of 49 CFR (DOT regulation), International Air Transport Association (IATA), and Deuche Forschungsgemeinschaft (DFG) regarding concentrations of emitted substances.

This product does not contain mercury and lithium-metal.

#### **Section 12 Ecological Information**

No materials contained in this product are bioaccumulativeo. No risk to persons or the surrounding environment.

#### **Section 13 Disposal Considerations**

- ► This product do not contain hazardous materials according to EC directives91/157/EEC and 93/86/EEC.
- ▶ Dispose of or recycle in accordance with appropriate local regulations.

#### **Section 14 Transport Information**

#### **IMDG NOT REGULATED**

Shipping Name: Not relevant
Hazard Class: Not relevant
UN Number / IATA Class Not relevant
Packing Group: Not relevant

The product is not listed as a dangerous product according to transport regulations

No.PM2015043 MSDS

## RID/ADR IMDG and ICAO.

Section 15 Regulatory Information					
OSHA hazard communication standard (29 C	FR 1910.1200)				
Hazardous	√Non-hazardous				
Section 16 Other Information					

This information relates only to the REACH regulation and specific material designated and may not be valid for such material used in combination with any other materials. Such information is to the best of our knowledge and is just used for health, safety and environmental purpose. It shall not be treated as any form of warranty. Please provide a proper training to the person who may use, manage of this material and those safety-handling persons.