

# Midmark IQspiro®

## Technical Specifications

Features	
Usage	Easy to use, digital diagnostic spirometer
Graphics	Real time graphics – Flow-Volume, Volume-Time
Reports	Full size 8.5 x 11 inches, customizable and preprogrammed
Predicted equations	Adult: Crapo (Crapo/Knudson compilation, aka ITS, ATS), Knudson (1976 & 1983 compilation), European Community For Coal And Steel (ECCS) (1993), NHANES III (aka NLHEP, Hankinson), Morris, Roca  Pediatric: Wang (1993), Knudson (1976 & 1983 compilation), Polgar (1971), Hsu, NHANES III, Zapletal, Eigen
Interpretation	NHANES III (NLHEP); ATS
Patient incentive screens	Candles, Thermometer, Tree & leaves, Tree, Leaves & monkeys, Tree, Leaves & pinwheel
Disposable Mouthpiece (DM)	Minimizes the chance of cross-contamination
EHR/EMR	Field proven seamless integration with more than 80 EHR/EMRs
Spirometry measurement principle	Fleisch Pneumotach – differential pressure reading of flow with a DM Volume determined by flow integration
Measuring Ranges	<ul style="list-style-type: none"> <li>• +/- 14 L/s – Flow</li> <li>• +/- 8 L – Volume</li> </ul>
Operating Conditions	<ul style="list-style-type: none"> <li>• 15° C to 40° C</li> <li>• 10% to 90% Humidity, non-condensing</li> </ul>
Analysis & Measurement	<ul style="list-style-type: none"> <li>• Automatic Back Extrapolation calculation</li> <li>• Automatic Spirometry parameter calculation</li> <li>• Automatic comparison to published Spirometry Predicted Equations (Reference Values)</li> <li>• Automatic interpretation of test results</li> </ul>
Parameters Measured	FVC, FEV.5, FEV1, FEV3, FEV6, FEV1/FVC, FEV3/FVC, FEV1/FEV6, FEV25%, FEV50%, FEV75%, FEV75-75%, FEV75-85%, FEV200-1200, FEV0.5/FIV0.5, PEF, FIVC, FIV0.5, FIF50%, PIF, Exp Time, V ext, MVV, MTV, RR, AT, AT%, VC, ERV, IRV, TV
Patient Contact	Single-use, disposable mouthpiece (Pneumotach)
Warranty	One (1) year
Physical Characteristics	
Dimensions	7.75" x 2.5" x 1.75", 191 x 64 x 44 mm
Weight	9 oz.
Calibration	3-liter syringe
Power	USB port

For additional product information, contact Midmark Corporation at 1-800-624-8950, option 2.  
 Midmark Corporation, 690 Knox Street, Suite 100, Torrance, California 90502  
[midmark.com](http://midmark.com)

53-79-90000267 Rev. D

