

Innovative New POC with the Established Reliability of the Oxlife Independence®

- Remote Monitoring via Cellular Connectivity and DNA Technology®
- Efficient Performance and Longer Battery Life with Energy Smart Technology®
- Lightweight and Durable
- Simple Control Functions with LCD Screen
- Battery Chargeable While Unit in Operation



OXLIFE
FREEDOM®



[Click here to view detailed product information and pricing.](#)

Call 800-397-5899 to order today!

PRODUCT SPECIFICATIONS¹

Dimensions	Height: 9.4" • Width: 9.0" • Depth: 3.4"
Weight	Device: 4.53 lbs • Battery: 1.35 lbs
Battery Duration	Up to 4.5 hours
Battery Recharge Time²	2 hours on AC or DC power
Oxygen Concentration	87% - 95% at sea level at all settings
Pulse Flow Settings³	1 - 5 with bolus size of 10 - 44ML
User Interface	Color LCD screen with keypad controls
AC Power	Universal Input: 100 - 240V, 50/60Hz Output: 24V, 6.3A Maximum Power Consumption: 150W
DC Power	Input: 11.5 - 16V, 18A Max Output: 19V, 6.3A Maximum Power Consumption: 120W
Operating Temperature	50°F (10°C) to 104°F (40°C)
Altitude Operating Range	0 - 13,123 feet (0 - 4,000 meters)
Transportation/Storage Humidity	0 - 95% non-condensing

¹ O2 Concepts® reserves the right to revise specifications at anytime without notice

² Battery recharge time will increase if unit is operating on DC power while charging

³ Bolus size based on 20 breaths per minute



O2-CONCEPTS.COM | 877.867.4008

© 2018 O2 Concepts, LLC; all rights reserved; O2 Concepts®, Oxlife Independence®, Oxlife Freedom®, DNA Technology® and Energy Smart Technology®, including certain related logos, are registered trademarks of O2 Concepts, LLC and may not be reproduced without express written consent.