



With rugged construction to endure demanding washdown environments, PT stainless steel platform scales provide the ultimate in durability for a variety of commercial, industrial and mining applications. PT stainless steel platforms offer a capacity up to 10000lb/4500kg and a readability of up to 0.5lb/0.2kg, and are available in three square platform sizes: 39in/1000mm; 47in/1200mm; and 59in/1500mm. Ideal for weighing food products, chemicals, pharmaceuticals or mining materials, the PT stainless steel platform features an IP66-rated load cell and stainless steel junction box, sealed for protection against water and dust. Easy to clean, the grade 304 stainless steel plate can tolerate frequent washing, while the sleek brushed surface helps prevent the accumulation of food and dirt particles. The PT stainless steel scale is supported by a reinforced frame beneath the platform, allowing the scale to accommodate substantial loads. Offering solid, dependable stability, PT stainless steel's heavy-duty rubber feet are adjustable to compensate for uneven weighing surfaces. Optional ramps are tailor-made to fit the exact size of each platform. PT stainless steel platform can be paired with the AE 402 indicator to provide the features and functions needed for any demanding washdown weighing task.

## IP66-rated platform ideal for washdown environments



### Features

- Rugged stainless steel construction for ultimate durability
- Approximately three-meter/10-foot shielded cable
- Can be used with any Adam indicators
- Heavy-duty rubber feet ensure stability of unit
- IP66-rated for protection against water and dust

### Applications

- Weighing
- Parts counting
- Checkweighing
- Dynamic / animal weighing

### Compatible Indicators



AE 402 Indicator

### About ADAM:

For more than 40 years, professionals worldwide have relied on Adam Equipment for an extensive selection of dependable and affordable weighing equipment. Adam provides the right balance of speed, performance and value.

# PT Stainless Steel Platforms

Model	PT 110S	PT 310S	PT 310-5S	PT 310-10S	PT 112S	PT 312S	PT 312-5S	PT 312-10S	PT 115S	PT 315S	PT 315-5S	PT 315-10S
<b>Capacity</b>	2500lb / 1000kg	5000lb / 3000kg	5000lb / 3000kg	10000lb / 4500kg	2500lb / 1000kg	5000lb / 3000kg	5000lb / 3000kg	10000lb / 4500kg	2500lb / 1000kg	5000lb / 3000kg	5000lb / 3000kg	10000lb / 4500kg
<b>Readability</b>	0.5lb / 0.2kg	1lb / 0.5kg	1lb / 0.5kg	2lb / 1kg	0.5lb / 0.2kg	1lb / 0.5kg	1lb / 0.5kg	2lb / 1kg	0.5lb / 0.2kg	1lb / 0.5kg	1lb / 0.5kg	2lb / 1kg
<b>Excitation Voltage</b>	5 - 10 VAC / DC											
<b>Loadcells</b>	4											
<b>Pan Size</b>	39.4"x39.4" / 1000x1000mm				47.2"x47.2" / 1200x1200mm				59.1"x59.1" / 1500x1500mm			
<b>Stabilization Time (sec)</b>	2											
<b>Power Supply</b>	N/A											
<b>Operating Temperature</b>	-10° to 40°C / 14° to 104°F											
<b>Housing</b>	Stainless steel											
<b>Cable Length</b>	10ft											
<b>Overall Dim.</b>	39.4"x39.4"x4.3" / 1000x1000x110mm (wxdxh)				47.2"x47.2"x4.3" / 1200x1200x110mm (wxdxh)				59.1"x59.1"x4.3" / 1500x1500x110mm (wxdxh)			
<b>Net Weight</b>	136.6lb / 62kg				174.1lb / 79kg				244.6lb / 111kg			

## Accessories

Item number	Description
700100203.....	Stainless Steel Ramp - PT 12RS 1200mm wide
700100204.....	Stainless Steel Ramp - PT 15RS 1500mm wide
700100202.....	Stainless Steel Ramp - PT 10RS 1000mm wide
2050013351.....	Indicator stand
700660289.....	Calibration certificate

Supplied by